

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600254
- **Trade name:** 1-K Anti-Rust Primer E-COLL
- **Article number:** 4317784305495
- **UFI:** MU0R-S4AG-SC01-9C3R
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
  - SU21 Consumer uses: Private households / general public / consumers
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Primer/adhesion promoter
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  - E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
  - EDE Platz 1
  - D-42389 Wuppertal
  - Germany
  
  - Tel. +49 202 6096-0
  - e-mail: [sdb@ede.de](mailto:sdb@ede.de)
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:**
  - Poison Control Center Mainz - 24 hour emergency service – phone: +49 (0) 6131/19240

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**

The labelling of an aspiration hazard (Asp.Tox.1 H304) is not required for aerosol dispensers and containers with a sealed spray device (Regulation (EC) 1272/2008, Annex 1,1.3.3).

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS09

**· Signal word** Danger**· Hazard-determining components of labelling:**

acetone

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

n-butyl acetate

butan-1-ol

**· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards**

The mixture does not contain any substance with endocrine disrupting properties (&lt; 0.1%).

**· Results of PBT and vPvB assessment****· PBT:**

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or does not fall under Annex XIII of Regulation (EC) 1907/2006 (&lt; 0.1%).

(Contd. on page 3)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 2)

**vPvB:**

The mixture does not contain a vPvB substance (vPvB = very persistent, very bioaccumulative) or does not fall under Annex XIII of Regulation (EC) 1907/2006 (< 0.1%).

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**
**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	20-30%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	10-20%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-10%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-10%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-10%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	0.978%

(Contd. on page 4)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 3)

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · **General information:**

Personal protection for the First Aider.  
Immediately remove any clothing soiled by the product.

##### · **After inhalation:**

Supply fresh air.  
Seek medical treatment in case of complaints.

##### · **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

##### · **After swallowing:**

Rinse out mouth and then drink plenty of water.  
Seek immediate medical advice.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

#### · 5.3 Advice for firefighters

##### · **Protective equipment:**

Do not inhale explosion gases or combustion gases.  
Mouth respiratory protective device.

##### · **Additional information**

Cool endangered receptacles with water spray.

(Contd. on page 5)

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 4)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation

**· 6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow product to reach sewage system or any water course.  
Do not allow to enter sewers/ surface or ground water.

**· 6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Dispose contaminated material as waste according to section 13.

**· 6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

**· 7.1 Precautions for safe handling**

Open and handle receptacle with care.  
Use only in well ventilated areas.

**· Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

**· Information about storage in one common storage facility: Store away from oxidising agents.**

(Contd. on page 6)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 5)

**Further information about storage conditions:**

Keep container tightly sealed.  
Protect from heat and direct sunlight.

**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 115-10-6 dimethyl ether**IOELV Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm**CAS: 67-64-1 acetone**IOELV Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm**CAS: 123-86-4 n-butyl acetate**IOELV Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm**CAS: 1330-20-7 xylene**IOELV Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
Skin**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see section 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Keep away from foodstuffs, beverages and feed.

**Respiratory protection:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device in case of insufficient ventilation.  
Self-contained respiratory protective device.

**Hand protection**

Protective gloves

**Material of gloves**

Butyl rubber, BR

(Contd. on page 7)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 6)

Recommended thickness of the material:  $\geq 0.4$  mm**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye/face protection**

Tightly sealed goggles

**· Body protection: Protective work clothing****SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information**

· Colour:	Grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol %
· Upper:	18.6 Vol %
· Flash point:	-41 °C
· Auto-ignition temperature:	235 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Kinematic: 23 °C - 4 mm (ISO 2431)	
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	4,000 hPa
· Density and/or relative density	
· Density at 20 °C:	0.83 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.

**· 9.2 Other information****· Appearance:****· Form:** Aerosol

(Contd. on page 8)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 7)

**· Important information on protection of health and environment, and on safety.**

- |                            |                              |
|----------------------------|------------------------------|
| · Ignition temperature:    | Product is not selfigniting. |
| · Explosive properties:    | Not determined.              |
| · Solvent separation test: |                              |
| · VOC (EC) %               | 85.10 %                      |
| · VOC (EC) g/l             |                              |
| · Solids content:          | 16.1 %                       |
| · Change in condition      |                              |
| · Drip point:              |                              |
| · Oxidising properties     | Not determined.              |
| · Evaporation rate         | Not applicable.              |

**· Information with regard to physical hazard classes**

- |   |   |
|---|---|
| · Explosives  | Void  |
| · Flammable gases   | Void  |
| · Aerosols  | Extremely flammable aerosol. Pressurised container:<br>May burst if heated. |
| · Oxidising gases   | Void  |
| · Gases under pressure  | Void  |
| · Flammable liquids   | Void  |
| · Flammable solids  | Void  |
| · Self-reactive substances and mixtures                                     | Void  |
| · Pyrophoric liquids  | Void  |
| · Pyrophoric solids   | Void  |
| · Self-heating substances and mixtures                                      | Void  |
| · Substances and mixtures, which emit flammable gases in contact with water | Void  |
| · Oxidising liquids   | Void  |
| · Oxidising solids  | Void  |
| · Organic peroxides   | Void  |
| · Corrosive to metals   | Void  |
| · Desensitised explosives   | Void  |

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 9)



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 8)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

**CAS: 115-10-6 dimethyl ether**

Inhalative	LC50/4h	308 ppm (rat)
------------	---------	---------------

**CAS: 67-64-1 acetone**

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4h	76 mg/m <sup>3</sup> (rat)

**CAS: 123-86-4 n-butyl acetate**

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	>21 ppm (rat)

**CAS: 1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

**CAS: 1314-13-2 zinc oxide**

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

**CAS: 71-36-3 butan-1-ol**

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h	8,000 ppm (rat)

**CAS: 7779-90-0 trizinc bis(orthophosphate)**

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

**CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)**

Oral	LD50	11,400 mg/kg (rat)
Dermal	LD50	22,800 mg/kg (rabbit) (GESTIS)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.

(Contd. on page 10)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 9)

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

**· Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information****· 12.1 Toxicity****· Aquatic toxicity:****CAS: 67-64-1 acetone**

LC50 (96h)	5,000 mg/L (Lepomis macrochirus)
LC50/48h	8,800 mg/l (Daphnia magna)
NOEC	430 mg/l (algae)
NOEC/16h	1,700 mg/l (Pseudomonas putida)
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)
96h LC50	5,540 mg/l (Oncorhynchus mykiss)

**CAS: 123-86-4 n-butyl acetate**

LC50 (96h)	18 mg/L (Pimephales promelas)
EC50 (48h)	44 mg/L (Daphnia magna)
EC50/24h	73 mg/l (Daphnia magna)
EC50/72h	647.7 mg/l (S)

**CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )**

EC50 (48h)	2.8 mg/L (daphnia)
96h LC50	3.6 mg/l (Leuciscus idus auratus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 11)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 10)

**· 12.5 Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**· 12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**· 12.7 Other adverse effects****· Additional ecological information:****· General notes:**Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.**SECTION 13: Disposal considerations****· 13.1 Waste treatment methods:****· European waste catalogue**

16 05 04\* gases in pressure containers (including halons) containing hazardous substances

**SECTION 14: Transport information****· 14.1 UN number or ID number****· ADR, IMDG, IATA**

UN1950

**· 14.2 UN proper shipping name****· ADR**

UN1950 AEROSOLS

**· IMDG**

AEROSOLS

**· IATA**

AEROSOLS, flammable

**· 14.3 Transport hazard class(es)****· ADR****· Class**

2 5F Gases.

**· Label**

2.1

(Contd. on page 12)

EU

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 11)

**· IMDG**

- Class
- Label

2.1 Gases.  
2.1

**· IATA**

- Class
- Label

2.1 Gases.  
2.1

- 14.4 Packing group
- ADR, IMDG, IATA

Void

- 14.5 Environmental hazards:
- Marine pollutant:

No  
Symbol (fish and tree)  
Symbol (fish and tree)

- Special marking (ADR):

- 14.6 Special precautions for user
- Hazard identification number (Kemler code):
- EMS Number:
- Stowage Code

Warning: Gases.  
-  
F-D,S-U  
SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

- 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

(Contd. on page 13)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 12)

**· Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **Transport category** 2
- **Tunnel restriction code** D

- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
acetone  
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )  
n-butyl acetate  
butan-1-ol
- **Hazard statements**  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 14)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 13)

- P280 Wear protective gloves / eye protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**• Chemical safety assessment****• Named dangerous substances - ANNEX I Methanol****• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t****• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t****• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3****• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**• REGULATION (EU) 2019/1148****• Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**• Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

CAS: 67-64-1 | acetone

**• Regulation (EC) No 273/2004 on drug precursors**

CAS: 67-64-1 | acetone

3

**• Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

CAS: 67-64-1 | acetone

3

**• National regulations:****• Information about limitation of use:**

Employment restrictions concerning pregnant and lactating women must be observed.

**• Exposure scenario(s)**Exposure scenario(s) of ingredients (if present) are available on request at:  
sdb@ede.de**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**• Relevant phrases**

- H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.

(Contd. on page 15)

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.01.2025

Version number 312 (replaces version 311)

Revision: 07.01.2025

**Trade name: 1-K Anti-Rust Primer E-COLL**

(Contd. of page 14)

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH205 Contains epoxy constituents. May produce an allergic reaction.

• **Department issuing SDS:** Product safety department

• **Contact:** sdb@ede.de

• **Date of previous version:** 01.02.2021

• **Version number of previous version:** 311

• **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

• **\* Data compared to the previous version altered.**