





LABEL: 6 red axially applied stripes on black cover "Continental TRIX ROTSTRAHL® DN 13 PN 20 BAR / 290 PSI Made in Germany"

## **APPLICATIONS**

Agricultural sector, Fleets, General industry, Industry, Landscaping and gardening, Mining industry, Municipal enterprises, Over- and underground workings, Workshops

## **FLOW MEDIUM**

Cooling water, Water

## **DESCRIPTION**

Inner lining: EPDM, black, non-porous, smooth

**Reinforcements:** Synthetic fibres

**Cover:** EPDM, black, smooth, from DN 28 upward fabric patterned, resistant

to ozone, weather and UV

Working pressure 20 bar / 290 psi

up to:

**Temperature** from -40 °C / -40 °F up to +100 °C / +212 °F

range:

**Further** Highly flexible

**properties:** Low resistance to flow

Robust

Up to DN 25 release agent- and fat free, free from product harmful to  $\,$ 

lacquer

## **TECHNICAL DATA**

nominal width	inner-Ø mm	wall thickness mm	outer-Ø mm	<b>length</b> m	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch					bar	psi	bar	psi	aprx. mm	aprx. g/ m
5/8	16	3.5	23	40	20	290	60	870	60	330
3/4	19	4	27	80	20	290	60	870	65	435
1	25	4.5	34	50	20	290	60	870	110	580
1 1/4	32	5.5	43	40	15	218	45	653	170	890
1 9/16	40	6	52	40	15	218	45	653	240	1150

 $Pressure\ based\ on\ room\ temperature\ /\ High\ pressure\ and/or\ temperature\ lead\ to\ reduced\ component\ durability$