

INTENSIVE SV1

Alcaline special cleaning agent - concentrate.

A liquid, alkaline, mildly foaming cleaning agent for removing oil, grease, soot, and mineral deposits, from all alkali-resistant surfaces.

Effective against: Oil; Grease; Soot; Mineral deposits

Field of use:

- Workshops: to remove and grease from floors
- **Engine or chassis repair or maintenance:** to remove oil and grease for cleanup or before repairs are done.
- Industrial and manufacturing plants: to remove oil and grease before surface painting.
- **Restaurant Drive-Through lanes:** where cars waiting for food have dropped oil and grease on the ground.

Product benefits:

- Efficient and Economical to use because the product is especially formulated for use with High Pressure Washers and Floor Care machines.
- Safe to use because of the high degree of Biodegradability and moderate pH.
- Reduced equipment maintenance because the formula includes corrosion and calcification blocking components.

Application:

- **High Pressure Washers:** Can be poured directly into the machine's detergent container, and applied at a dosing rate of 1-5%
- Floor Care Machines: For 'maintenance' cleaning, dilute between 1:20 (5%) and 1:10 (10%). For heavy-duty cleaning, dilute between 1:10 (10%) and 1:3 (33%).
- Pre-spraying: Dilute between 1:10 (10%) and 1:100 (1%), depending upon the soiling.
- For painted surfaces, maximum concentration is ~1%
- Automotive paint compatibility tested by Institute for Paint Testing (Giesen, Germany) Suitable for use in foodstuffs industries (Labor Dr. Boehm, Munich)

pH value: 10,0 (1% solution)

Order data: 4 x 2.5 l – Item. No. 105301646; 10 l – Item. No. 105301644; 25 L – Item. No. 105301645; 220 kg

Item. No. 105301643; 1000 kg – Item. No. 105301647

Notes:

UN Number: na Class / Packing Group: na









